

Powerful Performance and Exceptional Style



PATHRIDER 140 XL

4-Wheel Scooter



The Pathrider® 140 XL is an exciting blend of power and precision that features a 24-volt DC motor, full suspension, 33 cm (13") pneumatic tyres and a hydraulic-sealed brake system. Standard luxury touches, including an infinite adjustable wraparound easy-drive tiller, high-back pillow-top seat and LED lighting make it the perfect outdoor scooter.




Full Suspension

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

supplied and serviced by
Summerland Scooters and Rehab

Pathrider 140 XL

Specifications

Weight Capacity	181 kgs (400 lbs.)
Maximum Speed ¹	Up to 10 km/h (6.2 mph)
Ground Clearance ²	13.33 cm (5.25")
Turning Radius ²	Right: 210.8 cm (83") Left: 208.3 cm (82")
Overall Length ²	142.8 cm (56.25")
Overall Width ²	69.2 cm (27.25")
Front Tyres	10 x 33 cm (4" x 13") pneumatic
Rear Tyres	10 x 33 cm (4" x 13") pneumatic
Range Per Charge ^{2,4}	Up to 35 km (21.70 miles) (with 75 AH batteries)
Total Weight Without Batteries	117.70 kg (259.5 lbs.)
Heaviest Piece When Disassembled	93.21 kg (205.5 lbs.) (mid-frame)
Standard Seating	Type: Pillow-top Weight: 21.77 kg (48 lbs.) Material: Black vinyl Dimensions: Width: 49.5 cm (19.5") Depth: 44.5 cm (17.5")
Motor Output	24-volt DC motor, rear-wheel drive, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: 70 AH (standard) Weight: 70 AH: 25 kg (55 lbs.) each
Battery Charger	Off-board, 8 amp
Suspension	Front and rear
Seat-To-Floor Height	72.39 - 68.58 cm (28.5" - 27")
Colour Options	

Features

- Full suspension for optimum handling
- Sealed hydraulic brakes
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package, including directional signals and headlight
- Easy-drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror (standard)
- Front shield (standard)
- Pillow-top seat

Accessories

- Pride rear bag/walking stick holder
- Walker holder*
- Oxygen tank holder*
- Mobile Phone holder
- Cup holder
- Saddle bag
- Flag

**Must have Pride rear bag to attach*

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

Summerland Scooters and Rehab
The Plaza

Alstonville NSW 2477

phone: 02 6628 3915

www.summerlandscooters.com.au

Pride®
Mobility Products
Australia Pty. Ltd.