

Supreme Performance, Exhilarating Style, *And Excellent Value.*



PATHRIDER **10**
DELUXE

4-Wheel Scooter



Easy-Drive Tiller

The sleek, sporty **Pathrider® 10 Deluxe** scooter delivers smooth performance and all-new features. With a full complement of advanced standard features including rugged suspension, a high-visibility automatic front and rear lighting system, feather-touch disassembly, an LED kerb light, and a wraparound easy-drive tiller, the Pathrider 10 Deluxe is a greater value than ever before.

Summerland Scooters and Rehab
The Plaza, Alstonville, NSW, 2477
phone: 02 6628 3915
summerlandscooters.com.au

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

Specifications 4W: SC710DXAU

Weight Capacity	159 kg (350 lbs.)
Maximum Speed ¹	Up to 8.5 km/h (5 mph)
Ground Clearance ²	8.2 cm (3.2")
Turning Radius ²	157.5 cm (62")
Overall Length ²	119 cm (47")
Overall Width ²	56.5 cm (22")
Front Tyres	9 cm x 25 cm (3.5" x 10") solid
Rear Tyres	10 cm x 25 cm (4" x 10") solid
Suspension:	Front and Rear
Range Per Charge ^{2,4}	Up to 25 km (15.5 miles)
Total Weight Without Batteries	63.5 kg (140 lbs.)
Heaviest Piece When Disassembled	32 kg (71 lbs.) front section
Standard Seating	<i>Type:</i> Reclining high-back seat with headrest <i>Weight:</i> 13 kg (28 lbs.) <i>Material:</i> Black Vinyl <i>Dimensions:</i> Width: 46 cm (18") <i>Depth:</i> 43 cm (17")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Electronic, regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: 35AH (standard) or 40 AH (optional) Weight: 35 AH: 15 kg (32.5 lbs.) each 40 AH: 15 kg (32.5 lbs.) each
Battery Charger	Off-board, 3-amp
Colour	Viper Blue



NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

Features

- Front and rear suspension
- High-visibility automatic front and rear lighting system
- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Long-lasting, high-intensity LED headlight, tail light and indicators
- Exclusive stylish, lightweight, non-marking wheels
- Auto-connecting front-to-rear harness
- Easy-drive tiller with wraparound handles
- Backlit battery meter for increased accuracy and visibility in any setting
- Includes pinchless hinges and eight-position seat rotation
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual voltage off-board charger
- Rearview mirror standard

Options

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.