

4-WHEEL SCOOTER

# REVO®

SLEEK STYLING  
AND SUPER  
PORTABILITY

The **Revo** delivers full-sized scooter style, performance and features in a compact, lightweight design that easily disassembles for transport while remaining highly affordable.



Summerland Scooters and Rehab  
Alstonville Plaza  
Alstonville NSW 2477  
Phone: 02 6628 3915  
Email: [summerlandscooters@bigpond.com](mailto:summerlandscooters@bigpond.com)  
[www.summerlandscooters.com.au](http://www.summerlandscooters.com.au)

© 2014 PRIDE MOBILITY SCOOTERS. ALL RIGHTS RESERVED.  
**PRIDE® MOBILITY SCOOTERS**  
LIVE YOUR BEST®

# SPECIFICATIONS

**REVO®**

**4-wheel**

Weight capacity:	136 kg (300 lbs.)
Maximum speed <sup>1</sup> :	Up to 7.24 km/h (4.5 mph)
Ground clearance <sup>2</sup> :	6 cm (2.36") at frame
Turning radius:	127 cm (50")
Overall length <sup>2</sup> :	114 cm (44.9") / 55 cm (21.7")
Overall width <sup>2</sup> :	55 cm (21.7")
Front tyres:	5 cm x 19 cm (2" x 7.5") solid
Rear tyres:	5 cm x 23 cm (2" x 9") solid
Suspension:	N/A
Range per charge <sup>1,4</sup> :	Up to 32 km (20) miles
Total weight without batteries <sup>5</sup> :	53.5 kg (117 lbs.)
Heaviest piece when disassembled:	21.8 kg (48 lbs.) front section
Standard seating:	Type: Foldable molded plastic Material: Black Vinyl Dimensions: Width: 43 cm (17"), Depth: 41 cm (16")
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes:	Regenerative and electromechanical
Battery requirements <sup>3</sup> :	(2) 12-volt, deep cycle Size: (2) 35 AH (U-1) Weight: 11 kg (24.5 lbs.) each
Battery charger:	3.5-amp, off-board

Colour:



Red

## FEATURES

- Exclusive black, non-scuffing tyres
- Innovative interlocking drop-in battery packs for easy removal/installation
- Easily disassembles into five lightweight, easy-to-manage pieces
- 136 kg (300 lbs.) weight capacity
- State-of-the-art, microprocessor-based motor controller
- Seat offers height adjustment, 360° rotation and flip-up armrests for optimal user comfort
- Adjustable tiller for maximum comfort
- Headlight and taillight for added safety
- Easily-accessible charger port and circuit breaker



- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity
- 5 Battery weight may vary based on manufacturer.

**NOTE: All specifications subject to change without notice.**

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

**Pride**  
Mobility Products  
Australia Pty. Ltd.  
— LIVE YOUR BEST —

**PRIDE® MOBILITY SCOOTERS**  
LIVE YOUR BEST®



Quality  
Endorsed  
Company  
9001 95C20028  
SAI Global